

<b>Name</b>	<b>MURO ANTICO ESPRIT CHIC MURO ANTICO</b>
<b>Description</b>	Continuous acrylic coating with antique effect.
<b>Main Features</b>	Provides smooth old effect to the wall. Easy to apply. To be finished with Dolce Vita Velatura Universale to obtain the best decorative effect.
<b>Baldini Tecnicolor</b>	
<b>Classification (UNI 8682)</b>	RPAC – Pigmented – G1- Smoothed - R1S1
<b>Application Cycle</b>	Ensure that the surface to be coated is clean, dry and without foreign matters.  NEW SURFACES: apply a first coat of Fissativo Acrilico . OLD AND DEGRADED SURFACES: Execute a perfect cleaning of the surface, removing any trace of previous paint and/or plaster, dirt, etc. by brushing down, sanding or steam cleaning as required. On dried surface, apply a first coat of Fissativo Acrilico.  APPLICATION. Float a first coat of Muro Antico on the surface using a stainless steel float in an even way. While product is still wet, work the surface with light crossing movements to obtain the desired structure. Leave it dry for at least 24 hours before application of the finishing coat of Dolce Vita Velatura Silossanica, coloured solution with antique effect: Use a sponge and make light circular movements. It is also possible to use brush or rag: apply regularly on all surface without insisting on any point. Leave it dry. The final effect is obtained after 3 – 4 hours after application of Dolce Vita Velatura Silossanica.
<b>Practical advices</b>	Keep away from frost, close the tin tightly after use. The surface must be wet in the moment of application. Do not apply on surfaces with reclaiming moisture. Do not apply on surfaces exposed to sun or wind or when temperature is very hot. New plasters should be well-blended as regards seasoning, new patches must be perfectly matured. Wash well tools with water just after use. Ambient and surface conditions: ambient temperature min. 10°C / max 35°C; ambient relative humidity: < 75%; surface temperature : min 10°C / max 35°;
<b>Safety data</b>	<ul style="list-style-type: none"><li>• Keep the tin tightly closed, upside down and protected from frost.</li><li>• Labelling not required</li><li>• User information is contained in the relevant safety sheet.</li><li>• Empty containers and containers with traces of dried product film must be disposed of according to local regulations.</li></ul>
<b>Tender Item</b>	Application of Esprit Chic Muro Antico with an average consumption of _____ l per sq. m, to be applied in two coats at a cost of € _____ per sq. m, including materials and labour and excluding scaffoldings and surface dressing.

<b>Specifications and other technical information</b>	<b>Method</b>	<b>Main Data at 20°C and 60% Relative Humidity</b>
Coat finish and aspect		Matt
Density g/ml	BVL 007 (UNI 8910)	1,550 ÷ 1,650
Viscosity		Paste
Calculated spreading rate per coat	BVL 059	1,5 - 1,6 Kg/ m <sup>2</sup> (abt 0,6 m <sup>2</sup> /Kg)
Flash point °C	BVL 046 (UNI 8909)	Not flammable
Shelf life (in a cool and dry place)	BVL 064 (UNI 10154)	At least 36 moths
Hard dry H	BVL 033	Max 12 h.
Dry to recoat H	BVL 037	After 12 h.
Exteriors \ Interiors		No \ Yes
Colours		White
Binder		Acrylic
Tool cleaner		Water
Thinner		Water
Application with stainless steel float		Ready to use

This information is based on our best technical and practical knowledge. However, since the actual conditions in which the products are used beyond our direct control, we provide no guarantee as to effectiveness of the advice and suggestions contained herein. If in doubt, it is advisable to conduct preliminary tests and/or call our technical service.

**Atova International**

2452 N. Harlem Ave.  
Elmwood Park, IL 60707  
Phone:1-866-452-9982  
Fax:1-708-452-8331  
[www.paintandplasters.com](http://www.paintandplasters.com)  
[techsupport@paintandplasters.com](mailto:techsupport@paintandplasters.com)

