

Name	WAX PRESTIGIO ANTICO CERA PER STUCCO VENEZIANO
Description	Protective wax for floated and stucco finishes
Main Features	Balanced blend of natural virgin waxes, in suspension in a solvent.
Baldini Tecnicolor	
Classification (UNI 8681)	
Application Cycle	Can be applied using a rag, pad, or plastering trowel. Only a single very thin coat need be applied. When it is properly dry buff up using a soft cloth, or orbital polisher operating at low rpm. Do not apply Cera per Stucco Veneziano on surfaces that are still damp.
Practical Advice	In summer this product may become too fluid. It is best to allow it to congeal in a cool place and to mix it again. Air rooms during application and before inhabiting them overnight. Clean tools used with solvent immediately after use. Ambient and surface conditions: Ambient Temperature : min 5°C / max 35; Ambient Relative Humidity: Can be applied in very damp settings. Surface Temperature : min. 5°C / max 35; Dry Surface.
Safety data	<ul style="list-style-type: none">• Keep the tin tightly closed, upside down and protected from frost.• Labelling required.• User information is contained in the relevant safety sheet.• Empty containers and containers with traces of dried product film must be disposed of according to local regulations.
Tender item	Application of PRESTIGIO ANTICO CERA PER STUCCO VENEZIANO with an average consumption of _____ l per sq. m, to be applied in two coats at a cost of € _____ per sq. m, including materials and labour and excluding scaffoldings and surface dressing.

WAX Prestigio Antico Cera per Stucco Veneziano

Schedule Code BV000535-GB

Rev. 02 dated 12.01.2004 Page 2 of 2

Specifications and other technical information	Method	Main Data at 20°C and 60% Relative Humidity
Coat finish and aspect		-
Density g/ml	BVL 007 (UNI 8910)	0,790 ÷ 0,830
Viscosity		Paste
Calcuated spreading rate	BVL 059	about 20 sqm/ lt
Flash point °C	BVL 046 (UNI 8909)	>21
Shelf life (in cool and dry place)	BVL 064 (UNI 10154)	At least 36 months
Exteriors / Interiors		No / Yes
Tool cleaner		White spirit Tre Palme
Application using a pad		Ready to use

This information is based on our best technical and practical knowledge. However, since the actual conditions in which the products are used beyond our direct control, we provide no guarantee as to effectiveness of the advice and suggestions contained herein. If in doubt, it is advisable to conduct preliminary tests and/or call our technical service.

Atova International

2452 N. Harlem Ave.
Elmwood Park, IL 60707
Phone: 1-866-452-9982
Fax: 1-708-452-8331
www.paintandplasters.com
techsupport@paintandplasters.com

